Kilz Universal Sealer Primer/Stain Masterchem Industries LLC Blocker

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name:

KILZ® Premium

MSDS Manufacturer

1300

Number: Manufacturer Name:

Masterchem Industries LLC

Address:

3135 Old Highway M Imperial, MO 63052-2834

General Phone Number:

(636) 942-2510

General Fax Number: Customer Service Phone

(636) 942-3663 (800) 325-3552

Number:

CHEMTREC:

For emergencies in the US, call CHEMTREC: 800-424-9300

Canutec:


In Canada, call CANUTEC: (613) 996-6666 (call collect)

MSDS Creation Date: MSDS Revision Date:

June 26, 2006 April 27, 2010

MSDS Format:

According to ANSI Z400.1-2004





Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

			NAME AND POST OF THE PARTY OF T
Chemical Name	CAS#	Ingredient Percent	Annual Control of the State of
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5 by weight	
Titanium dioxide	13463-67-7	10 - 30 by weight	
Ethylene glycol	107-21-1	1 - 5 by weight	
NJTS-50780-NLD	Proprietary	1 - 5 by weight	
NJTS-50761-NLD	Proprietary	10 - 30 by weight	
Nepheline Syenite	37244-96-5	5 - 10 by weight	
Non hazardous ingredient(s)	Not applicable	30 - 60 by weight	
Undisclosed/Proprietary	No data	1 - 5 by weight	

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Irritant.

Potential Health Effects:

Eye: May cause irritation.

Skin:

May cause irritation.

Inhalation:

Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion:

May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Signs/Symptoms:

Prolonged or repeated contact may cause skin irritation. Overexposure may cause headaches and dizziness.

Target Organs:

Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

None generally recognized.

SECTION 4 - FIRST AID MEASURES

Eye Contact:

Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact:

Immediately wash skin with soap and plenty of water.

Inhalation:

Get medical attention if irritation develops or persists.

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Other First Aid:

Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs

naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 - FIRE FIGHTING MEASURES

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

Extinguishing Media:

Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray

when fighting fires involving this material. Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH

(approved or equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:

Use proper personal protective equipment as listed in section 8.

Environmental Precautions:

Avoid runoff into storm sewers, ditches, and waterways

Spill Cleanup Measures:

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container Provide ventilation. Clean up spills immediately observing

precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling:

Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin

Storage:

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in

Hygiene Practices:

Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training,

inspection and maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN

166.

Skin Protection Description:

Respiratory Protection:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

A NIOSH approved air-purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne

concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide

adequate protection.

Other Protective:

Facilities storing or utilizing this material should be equipped with an eyewash

facility and a safety shower.

Silica, amorphous, precipitated and gel:

Guideline ACGIH:

TLV-TWA: 10 mg/m3

Guideline OSHA: Titanium dioxide:

OSHA-TWA: 20 mg/m3

Guideline ACGIH: Guideline OSHA:

TLV-TWA: 10 mg/m3 OSHA-TWA: 15 mg/m3

Ethylene glycol:

Guideline ACGIH:

TLV-STEL: C 100 mg/m3 (Aerosol only)

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:

Liquid. White

Boiling Point:

Color:

No Data No Data

Melting Point:

10 - 12 Lbs./gal.

Density: Vapor Density:

Greater than 1 (Air = 1).

pH: Molecular Formula:

8.5 to 9.5 Mixture

Molecular Weight:

Mixture

Flash Point:

No Data

Material VOC: 42 gm/l (Includes water) Coating VOC.: 95 gm/l (Excludes Water)

Chemical Stability:

Stable under normal temperatures and pressures.

Hazardous Polymerization:

Conditions to Avoid:

Heat, flames, incompatible materials, and freezing or temperatures below 32 deg.

Incompatible Materials:

Oxidizing agents. Strong acids and alkalis.

SECTION 11 - TOXICOLOGICAL INFORMATION

Silica, amorphous, precipitated and gel:

RTECS Number:

VV7315000

Titanium dioxide:

RTECS Number:

XR2275000

Skín:

Skin - Rabbit; Standard Draize Test. : 300 ug/3D; (Intermittent) mild. (RTECS) Ingestion - Rat TDLo: 60 gm/kg; Gastrointestinal - hypermotility, diarrhea

Ingestion:

Gastrointestinal - other changes. (RTECS)

Ethylene glycol:

RTECS Number:

KW2975000

Eye:

Eye - Rabbit; Standard Draize Test.: 500 mg/24H; mild.

Eye - Rabbit; Standard Draize Test.: 1440 mg/6H; Moderate. (RTECS) Skin - Rabbit; Open irritation: 555 mg; mild. (RTECS)

Inhalation:

Skin:

Inhalation - Rat LC: >200 mg/m3/4H; Details of toxic effects not reported other

than lethal dose value.

Inhalation - Mouse LC: >200 mg/m3/2H; Details of toxic effects not reported

other than lethal dose value. (RTECS)

Ingestion:

Ingestion - Rat LD50: 4700 mg/kg; Details of toxic effects not reported other

than lethal dose value.. (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:

No ecotoxicity data was found for the product.

Environmental Fate:

No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your

state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

auidelines.

DOT UN Number:

No Data

DOT Hazard Class:

No Data

SECTION 15 - REGULATORY INFORMATION

California PROP 65:

WARNING: This product contains a chemical known to the state of California to

cause cancer and birth defects or other reproductive harm.

Silica, amorphous, precipitated and gel:

TSCA Inventory Status:

Not listed Listed

Canada DSL: <u>Titanium dioxide</u>:

TSCA Inventory Status:

Listed

State Regulations:

Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

Ethylene glycol:

TSCA Inventory Status: Listed

State Regulations:

Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL:

Listed

Nepheline Syenite:

TSCA Inventory Status:

Not listed

Canada DSL:

Listed

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard:

1

HMIS Reactivity: 0
HMIS Personal Protection: x
HMIS Other: x

Disclaimer:

MSDS Creation Date: June 26, 2006 MSDS Revision Date: April 27, 2010

MSDS Revision Notes: Quarterly formula update
MSDS Author: Actio Corporation

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled

environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

Trademark: The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights

Reserved.

Copyright@ 1996-2010 Actio Software Corporation. All Rights Reserved.