# AIR INTAKE SYSTEM CLEANER

HMIS RATIN	G
Health	2
Flammability	4
Reactivity	0

MATERIAL SAFETY DATA SHEET

NFPA 704 RAT	ING
Health	2
Flammability	4
Reactivity	0
NFPA 30B LEV	/EL
3	

KIMBALL-MIDWEST P.O. BOX 2470 COLUMBUS, OH 43216-2470

CORPORATE TELEPHONE: 614-219-6100 EMERGENCY TELEPHONE: 800-424-9300

### 1. PRODUCT IDENTIFICATION

PART NUMBER	80-938
TAILT NONDEN	.00 730
PRODUCT NAME	Air Intaka Systom Claanar
PRODUCT INAIVIE	. All lillake system cleaner
CHEMICAL FAMILY	N/A
CHEMICAL LAMILL	.IN/ A
DOT SHIPPING	Limited Quantity (LQ)
DOI 31111 1 11VG	. Littlica Quartity (LQ)

#### 2. HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	ACGIH TLV	STEL	%
2-Propanone (67-64-1)	750ppm	750ppm	1000ppm	<60
Propane/Isobutane/n-Butane (68476-86-8)	800ppm	800ppm	-	<25
*Toluene (108-88-3)	100ppm	50ppm	150ppm	<20
*Xylene isomers (1330-20-7)	100ppm	100ppm	150ppm	<5
4-Hydroxy-4-Methyl-2-Pentanone (123-42-2)	50ppm	50ppm	-	<4
*Methyl Alcohol (67-56-1)	200ppm	200ppm	250ppm	<4
*2-Butanone (78-93-3)	200ppm	200ppm	300ppm	<4

All chemical compounds marked with an asterisk (\*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement. \*\*Ceiling

#### 3. PHYSICAL DATA

BOILING POINT (RANGE)	43 -334°F
VAPOR PRESSURE PSIG @ 70°F	.ND
VAPOR DENSITY (AIR = 1)	.>1
SOLUBILITY IN WATER	. Partial
SPECIFIC GRAVITY (H2O = 1)	.0.8600
MELTING/FREEZING POINT	.ND
EVAPORATION RATE (61%=1)	. Faster than Butyl Acetate
VOC content (by weight)	.44.2%
APPEARANCE AND ODOR	.Light amber liquid/ solvent
	odor

## 4. FIRE AND EXPLOSION DATA

FLASH POINT	15	6°F
UPPER EXPLOSIVE LIMIT (%)	36.0	)
LOWER EXPLOSIVE LIMIT (%)	1.0	
EXTINGUISHING MEDIA		e-fighting foam, CO <sub>2</sub> , dry emical, Water fog .
SPECIAL FIREFIGHTING PROCE	DURESCor if exposed to heat (fire	ntainers can build up pressure ). As in any fire, wear self- pparatus pressure-demand

contained breathing apparatus pressure-demand (MSHA/NIOSH) and full protective cans.

FIRE AND EXPLOSION HAZARDS......Vapors can travel to a sources of ignition and flash back. "Empty" containers retain

of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flamer sparks, static electricity or other sources of ignition; they may explode or cause injury or death. Empty drums should be drained, properly bunged

and promptly returned to a drum reconditioner, or promptly disposed of.

# 5. HEALTH EFFECTS DATA

5. F	IEALTH EFFECTS DATA
SHOP	RT TERM EFFECTS OF EXPOSURE
ROUTE OF ENTRY	Skin Contact, Skin Absorption, Inhalation, Ingestion and Eye Contact.
HEALTH HAZARDS	•
(ACUTE AND CHRONIC)	Overexposure may cause nervous system damage, lung damage and kidney damage.
EYE CONTACT	Irritation causes pain, tearing, reddening and swelling accompanied by stinging sensation.
SKIN CONTACT	Prolonged or repeated contact could cause defattting and drying of skin. Irritation to skin and dermatitis.
INGESTION	Harmful or fatal if swallowed. Corrosive and may cause severe & permanent damage to mouth, throat and stomach.
INHALATION	Headaches, dizziness, nausea, decrease blood pressure, changes in heart rate and cyanosis may result from

overexposure.

#### 5. HEALTH EFFECTS DATA CON'T

MEDICAL CONDITIONS GENERALLY		
AGGRAVATED BY EXPOSURE None Listed		

EYE CONTACT	FIRST AID PROCEDURES Hold eyelids apart and immediately flush eyes with plenty of water. Get medical attention, if irritation
	persists.
SKIN CONTACT	Immediately flush skin with plenty of water. Remove Clothing. Get medical attention immediately. Wash clothing separately before reuse.
INGESTION	Get medical attention immediately. If swallowed, DO NOT INDUCE VOMITING unless directed to do so by medical personnel. Never give anything by mouth to an unconscious victim or a person losing consciousness.
INHALATION	Remove the person away from exposure to fresh air. If not breathing give artificial respiration. If have trouble breathing, give oxygen. Get immediate medical attention.

#### SPECIAL HEALTH EFFECTS

STABILITY...

INCOMPATIBILITIES.

CARCINOGEN (OSHA Guidelines) .......This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

# 6. REACTIVITY Stable Strong acids, alkalis, oxidizers, and amines. All sources of ignition, welding arcs and open

conditions

HAZARDOUS POLYMERIZATION CONDITIONS..... None known.

#### 7. PRECAUTIONS FOR SAFE HANDLING & USE

7. FRECAUTIC	MOTOR SALETIANDLING & OSL
PROTECTIVE EQUIPMENT	_
REQUIREMENTS	Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during use. NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge. Where contact is expected wear chemical resistant gloves, a chemical suit, rubber boot, and chemical safety goggles and plus face shield.
WASH REQUIREMENTS	Wash with soap and water.
SPILL OR LEAK PROCEDURES	Absorb spill with inert material (e.g. dry sand or earth), then place in chemical waste container.
WASTE DISPOSAL METHODS	Dispose of in accordance with local, state, and federal regulations.
HANDLING & STORAGE	Wash thoroughly after handling. Do not allow to freeze. Avoid temperatures above 120°F
OTHER PRECAUTIONS	Use NIOSH approved respirator with an organic vapor cartridge; avoid prolonged breathing of vapors; protection provided by air purifying respirators is limited.

#### 8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.



Specializing in Materials Management since 1923