

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 1 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Paint Thinner
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Web site address: www.wmbarr.com
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Intended Use: Paint, stain, and varnish thinning.
Product Code: CKPT94402, EKPT94401, GKPT94002, GKPT94002P, GKPT94400, QKPT94003, QKPT94203, QKPT943

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 3
Acute Toxicity: Inhalation, Category 4
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2B
Germ Cell Mutagenicity, Category 1B
Toxic To Reproduction, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 2
Aspiration Toxicity, Category 1

**GHS Signal Word:****Danger****GHS Hazard Phrases:**

H226 - Flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.

H332 - Harmful if inhaled.
H336 - May cause drowsiness or dizziness.
H340 - May cause genetic defects .
H361 - Suspected of damaging fertility or the unborn child .
H373 - May cause damage to through prolonged or repeated exposure.

GHS Precautionary Phrases:

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition source. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting/.../equipment. ... other specified by the manufacturer/supplier or the competent authority.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 2 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

GHS Response Phrases:

P281 - Use personal protective equipment as required.
P235 - Keep cool.
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313 - IF exposed or concerned: Get medical attention/advice.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P314 - Get medical attention/advice if you feel unwell.
P321 - Specific treatment see ... on this label.
P331 - Do NOT induce vomiting.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P362 - Take off contaminated clothing and wash before re-use.
P370 - In case of fire:

GHS Storage and Disposal Phrases:

P403 - Store in well-ventilated place.
P405 - Store locked up.
P501 - Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation Acute Exposure Effects:
May cause dizziness, headache, watering of eyes, eye irritation, weakness, nausea, muscle twitches and depression of central nervous system. Severe over exposure may cause convulsions, unconsciousness and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal. Inhalation of decomposition products may cause severe injury or death.

Skin Contact Acute Exposure Effects:

May cause skin irritation. Decomposition may produce carbon monoxide and carbon dioxide. May cause numbness in fingers and arms, drying of skin, and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation, burns, conjunctivitis of eyes and corneal ulcerations of the eye. Vapors may irritate eyes. May cause jaundice, bone marrow damage, liver damage, anemia and skin irritation.

Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. May cause nausea; vomiting; weakness; muscle twitches; gastrointestinal irritation; diarrhea; unconsciousness; convulsions; and death.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. May cause jaundice, bone marrow damage, liver damage anemia and skin irritation.

Medical Conditions Generally Aggravated By Exposure:

Diseases of the skin, eyes, liver, kidneys central nervous system and respiratory system.

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 3 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	80.0 -100.0 %
25551-13-7	Benzene, Trimethyl-	3.0 -7.0 %

Additional Chemical Information Ingredients vary due to multiple blends and/or raw material suppliers.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Inhalation:
If user experiences breathing difficulty, move to air free of vapors. Administer oxygen if breathing is difficult. Skin Contact Acute Exposure Effects:

Skin Contact:
Wash with soap and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.

Eye Contact:
Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

Ingestion:
Do NOT induce vomiting. Call your poison control center, hospital emergency room, or physician immediately for instructions.

If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Signs and Symptoms Of Exposure:

ROUTE OF ENTRY: Inhalation, Skin/Dermal, Eye/Ocular, Ingestion/Oral.

Note to Physician:

Call your local poison control center for further information.

Inhalation: Inhalation overexposure can produce toxic effects. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation as required.

Ingestion: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 4 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

5. FIRE FIGHTING MEASURES

Flammability Classification: NFPA Class II

Flash Pt: > 100.00 F

Explosive Limits: LEL: 0.5 UEL: 6

Autoignition Pt:

Suitable Extinguishing Media: Use carbon dioxide, dry powder, or foam.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Flammable Properties and Hazards: Combustible. Liquid.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide, smoke, fumes and/or unburned hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Methods for cleaning up.

Material Is Released Or

Spilled: Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Stay upwind, out of low areas, and ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Spills/Leaks:

Take up with sand or other non-combustible absorbent material and place into containers for later disposal.

Dike to collect large liquid spills.

Dike far ahead of spill for later disposal.

WASTE DISPOSAL

Dispose in accordance with applicable local, state and federal regulations.

A single exposure, when used as directed, is not likely to result in adverse skin effects.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container. Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container. according to local, state and federal regulations. Do not reuse this container.

A static electrical charge can accumulate when this material is flowing through pipes, nozzles or filters, and when it is agitated. A static spark discharge can ignite accumulated vapors particularly during dry weather conditions. Always use proper bonding and grounding procedures.

Precautions To Be Taken in Keep container tightly closed when not in use. Store in a cool, dry place. Do not store

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 5 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

Storing: near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	ACGIH TLV	TLV: 100 ppm	
		OSHA PELs	PEL: 500 ppm	
25551-13-7	Benzene, Trimethyl-	ACGIH TLV	TLV: 25 ppm	
Respiratory Equipment (Specify Type):		For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For OSHA controlled workplace and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dusk mask does not provide protection against vapors. A dust mask does not provide protection against vapors.		
Eye Protection:		Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.		
Protective Gloves:				
Other Protective Clothing:		Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.		
Engineering Controls (Ventilation etc.):		Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.		
Work/Hygienic/Maintenance Practices:		A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use and before eating, drinking, or smoking.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Water white / Free and clear. Odor threshold not determined.
pH:	N.D.
Melting Point:	N.A.
Boiling Point:	318.00 F - 385.00 F
Flash Pt:	> 100.00 F
Evaporation Rate:	N.D.
Flammability (solid, gas):	
Explosive Limits:	LEL: 0.5 UEL: 6
Vapor Pressure (vs. Air or mm Hg):	0.3 MM HG at 68.0 F ND MM HG at 50.0 C
Vapor Density (vs. Air = 1):	5 Air = 1

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 6 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

Specific Gravity (Water = 1): 0.78

Solubility in Water: Slight

Solubility Notes: Very slightly soluble in cold water.

Saturated Vapor Concentration: N.D.

Octanol/Water Partition Coefficient: ND

Percent Volatile: 100.0 % by weight.

VOC / Volume: 778.0000 G/L

Autoignition Pt:

Decomposition Temperature: N.D.

Viscosity: N.D.

a_fld_hdr[9]: ND = Not Determined.
ND = Not Determined.

Information with regard to primary physical hazard:

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability:

Incompatibility - Materials To Avoid: Incompatible with strong acids, alkalies and oxidizers such as liquid chlorine and oxygen.

Hazardous Decomposition or Byproducts: Decomposition may produce carbon monoxide and carbon dioxide.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions:

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 7 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Information below will be for individual ingredients. Refer to section 2 for acute and chronic health effects.

CAS# 25551-13-7:
Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.
Result:
Kidney, Ureter, Bladder: Changes in liver weight.
Endocrine: Changes in thymus weight.
Immunological Including Allergic: Decreased immune response.
- "Sbornik Vysledku Toxikologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, 24 H, Mild.
Result:
Kidney, Ureter, Bladder: Changes in liver weight.
Kidney, Ureter, Bladder: Changes in bladder weight.
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.
- "Sbornik Vysledku Toxikologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}				
25551-13-7	Benzene, Trimethyl-				

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Flammable liquids, n.o.s. (Stoddard solvent, Benzene, Trimethyl-)
DOT Hazard Class: 3 FLAMMABLE LIQUID
UN/NA Number: UN1993 **Packing Group:** III



Additional Transport Information:

The shipper / supplier may be able to apply one of the following exceptions if allowed under 49 CFR Regulations: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49 CFR Hazmat Regulations. Please consult 49 CFR Subchapter C to ensure that subsequent shipments comply with these exceptions. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 8 of 8

Printed: 08/10/2023

Revision: 08/09/2023

Supersedes Revision: 11/22/2022

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	No	No	No

25551-13-7	Benzene, Trimethyl-	No	No	No
------------	---------------------	----	----	----

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	TSCA: Inventory
-----------	--	-----------------

25551-13-7	Benzene, Trimethyl-	TSCA: Inventory
------------	---------------------	-----------------

Regulatory Information: This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 08/09/2023 **Previous revision:** 11/22/2022

Preparer Name: W.M. Barr and Company, Inc. (901)775-0100

Additional Information About This Product:

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.