

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

## 1 Identification of the substance and manufacturer

Trade name: MRO STAINLESS STEEL

Product code: 0006201460  
 Product category: PC9a Paints and coatings.  
 Manufacturer/Supplier: Seymour of Sycamore



917 Crosby Avenue  
 Sycamore, IL 60178  
 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Carc. 2 H351 Suspected of causing cancer.  
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

Danger

### Hazard statements

Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Read label before use.

### Precautionary statements

Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Use personal protective equipment as required.  
 Do not breathe dust/fume/gas/mist/vapours/spray.  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If skin irritation occurs: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of water.  
 Take off contaminated clothing and wash before reuse.  
 IF exposed or concerned: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.  
 Specific treatment (see on this label).  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

|            |                       |        |
|------------|-----------------------|--------|
| 108-88-3   | Toluene               | 25.52% |
| 67-64-1    | Acetone               | 20.95% |
| 74-98-6    | propane               | 15.72% |
| 106-97-8   | n-butane              | 9.23%  |
| 65997-19-5 | Stainless Steel Flake | 7.06%  |
| 1330-20-7  | xylene (mix)          | 6.61%  |
| 64742-47-8 | Mineral Spirits       | 1.25%  |

(Contd. on page 2)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO STAINLESS STEEL

(Contd. of page 1)

100-41-4 ethyl benzene

1.17%

## 4 First-aid measures

|  |  |
|--|--|
| <b>After inhalation:</b>                                     | Supply fresh air; consult doctor in case of complaints.  |
| <b>After skin contact:</b>                                   | Immediately wash with water and soap and rinse thoroughly.<br>Remove contaminated clothing. Wash exposed area with soap and water. |
| <b>After eye contact:</b>                                    | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.                                   |
| <b>After swallowing:</b>                                     | Rinse out mouth and then drink plenty of water.<br>Rinse mouth with water. Do not induce vomiting.                                 |
| <b>Most important symptoms and effects:</b>                  | Dizziness  |
| <b>Indication of any immediate medical attention needed:</b> | No further relevant information available.   |

## 5 Fire-fighting measures

|   |  |
|---|--|
| <b>Extinguishing agents:</b>                  | CO2, extinguishing powder or water spray. Fight larger fires with water spray. |
| <b>Special hazards:</b>                       | Can form explosive gas-air mixtures.   |
| <b>Protective equipment for firefighters:</b> | A respiratory protective device may be necessary.                              |

## 6 Accidental release measures

|   |   |
|---|---|
| <b>Personal precautions, protective equipment and emergency procedures:</b> | Wear protective equipment. Keep unprotected persons away.<br>Use respiratory protective device against the effects of fumes/dust/aerosol. |
| <b>Methods and material for containment and cleaning up:</b>                | Ensure adequate ventilation.<br>Dispose contaminated material as waste according to section 13.   |

## 7 Handling and storage

|                                      |   |
|--------------------------------------|---|
| <b>Precautions for safe handling</b> | Use only in well ventilated areas.  |
| <b>Storage requirements:</b>         | Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.<br>Store locked up. |

## 8 Exposure controls/personal protection

### Components with limit values that require monitoring at the workplace:

#### 108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV (USA) Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
BEI

#### 67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV (USA) Short-term value: (1782) NIC-1187 mg/m<sup>3</sup>, (750) NIC-500 ppm  
Long-term value: (1188) NIC-594 mg/m<sup>3</sup>, (500) NIC-250 ppm  
BEI

#### 74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F

#### 106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm

#### 1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL (USA) Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV (USA) Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI

(Contd. on page 3)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO STAINLESS STEEL

(Contd. of page 2)

**100-41-4 ethyl benzene**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL (USA) | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm |
|           | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| TLV (USA) | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm    |
|           | BEI   |

**Ingredients with biological limit values:****108-88-3 Toluene**

|           |  |
|-----------|--|
| BEI (USA) | 0.02 mg/L<br>Medium: blood<br>Time: prior to last shift of workweek<br>Parameter: Toluene                      |
|           | 0.03 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Toluene   |
|           | 0.3 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: o-Cresol with hydrolysis (background) |

**67-64-1 Acetone**

|           |  |
|-----------|--|
| BEI (USA) | 50 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific) |
|-----------|--|

**1330-20-7 xylene (mix)**

|           |  |
|-----------|--|
| BEI (USA) | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----------|--|

**100-41-4 ethyl benzene**

|           |   |
|-----------|---|
| BEI (USA) | 0.7 g/g creatinine<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
|           | -<br>Medium: end-exhaled air<br>Time: not critical<br>Parameter: Ethyl benzene (semi-quantitative)  |

**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
Immediately remove all soiled and contaminated clothing.  
Wash hands after use.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**

|                                    |  |
|------------------------------------|--|
| <b>Appearance:</b>                 | Aerosol.   |
| <b>Odor:</b>                       | Aromatic   |
| <b>Odor threshold:</b>             | Not determined.  |
| <b>pH-value:</b>                   | Not determined.  |
| <b>Melting point/Melting range</b> | Undetermined.  |
| <b>Boiling point:</b>              | -110 °C (-166 °F)  |
| <b>Flash point:</b>                | -19 °C (-2 °F)   |
| <b>Flammability (solid, gas):</b>  | Extremely flammable.                                     |
| <b>Decomposition temperature:</b>  | Not determined.  |
| <b>Auto igniting:</b>              | Product is not self-igniting.                            |
| <b>Danger of explosion:</b>        | In use, may form flammable/explosive vapour-air mixture. |
| <b>Lower Explosion Limit:</b>      | 1.7 Vol %  |
| <b>Upper Explosion Limit:</b>      | 10.9 Vol %   |
| <b>Vapor pressure:</b>             | Not determined.  |
| <b>Relative Density:</b>           | Between 0.77 and 0.85 (Water equals 1.00)                |

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO STAINLESS STEEL

(Contd. of page 3)

**Vapour density:** Not determined.  
**Evaporation rate:** Not applicable.  
**Partition coefficient: n-octonal/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**VOC content:** 611.3 g/l / 5.10 lb/gl  
**VOC content (less exempt solvents):** 59.6 %  
**MIR Value:** 1.85  
**Solids content:** 20.8 %

## 10 Stability and reactivity

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

LD/LC50 values that are relevant for classification:

### 106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

### 1330-20-7 xylene (mix)

Oral LD50 8700 mg/kg (rat)

Dermal LD50 2000 mg/kg (rbt)

Inhalative LC50/4 h 6350 mg/l (rat)

### 100-41-4 ethyl benzene

Oral LD50 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rbt)

**Information on toxicological effects:** No data available.  
**Sensitization:** No sensitizing effects known.

### Carcinogenic categories

#### IARC (International Agency for Research on Cancer)

|           |               |    |
|-----------|---------------|----|
| 108-88-3  | Toluene       | 3  |
| 1330-20-7 | xylene (mix)  | 3  |
| 100-41-4  | ethyl benzene | 2B |

#### NTP (National Toxicology Program)

None of the ingredients is listed.

#### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**UN-Number:** UN1950  
**DOT:** Aerosols, flammable  
**ADR:** 1950 Aerosols  
**Transport hazard class(es):**  
**Class:** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U

(Contd. on page 5)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO STAINLESS STEEL

(Contd. of page 4)

Packaging Group: --  
 UN "Model Regulation": UN1950, Aerosols, 2.1

## 15 Regulatory information

### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

### SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

California Proposition 65 chemicals  
 known to cause developmental  
 toxicity:

Canadian WHMIS: 108-88-3 Toluene

D2A

### EPA:

108-88-3 Toluene

67-64-1 Acetone

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

II

I

I

D

USDA (United States Department of  
 Agriculture):

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

## 16 Other information

Contact: Regulatory Affairs

US4