PERFORMANCE PLUS

Performance Plus Natural Gas SAE 15W-40 CNG+

Safety Data Sheet

SDS ID: 820383

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Performance Plus Natural Gas SAE 15W-40 CNG+

Product Code

PP228154C

Synonyms

None known.

Product Use

If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

None known.

FOR PRODUCT MANUFACTURED IN THE U.S.A.:

MANUFACTURER SUPPLIER

Kleen Performance Products Safety-Kleen Canada, Inc.

2600 North Central Expressway 25 Regan Road

Suite 200 Brampton, Ontario, Canada L1A 1B2

Richardson, TX 75080

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURER SUPPLIER

Kleen Performance Products

Safety-Kleen Systems, Inc.

25 Regan Road

2600 North Central Expressway

Brampton, Ontario, Canada L1A 1B2 Suite 200

Richardson, TX 75080

www.safety-kleen.com

Phone: 1-800-669-5740 Emergency Phone #: 1-800-468-1760

Issue Date

February 6, 2019

Supersedes date

May 14, 2018

Original Issue Date

May 14, 2018

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

Skin Sensitization - Category 1

GHS Label Elements

Symbol(s)



Warning

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Hazard Statement(s)

May cause an allergic skin reaction.

Precautionary Statement(s)

Prevention

Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace.

Response

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Repeated exposure may cause skin dryness or cracking.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	75-80
64742-54-7	Distillates, petroleum, hydrotreated heavy paraffinic	4.5-7.5
Mixture	Highly refined mineral oil (C15-C50)	4 – 4.5
Trade Secret	01154100-5327P	1- 1.2
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	0.5 - 1

Further information

The chemical identity is being withheld as a trade secret.

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention, if needed.

Skin

IF ON SKIN: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most Important Symptoms/Effects

Acute

May cause allergic skin reaction.

Page 2 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Delayed

Repeated exposure may cause skin dryness or cracking.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, water fog. Water or foam may cause frothing.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Negligible fire hazard. Avoid friction, static electricity and sparks.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce oxides of carbon and unidentified organic compounds.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks and naked flames. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools and explosion-proof equipment. Use in a well ventilated area. Avoid contact with eyes Skin clothing shoes.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition.

Incompatible Materials

Strong oxidizing materials.

Page 3 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada and ACGIH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

Individual Protection Measures, such as Personal Protective Equipment

Eve/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

No respiratory protection is normally required. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended. When products are heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid	Physical State	Liquid
Odor	Not available	Color	Not available
Odor Threshold	Not available	рН	Not available
Melting Point	Not available	Boiling Point	Not available
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	210 °C
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available

Page 4 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Water Solubility
Not available
Partition coefficient: not available
Octanol/water
Not available

Viscosity 12.5 100 °C Kinematic viscosity Not available

Solubility (Other) Not available Density Not available

Physical Form Liquid Molecular Weight Not available

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition

Incompatible Materials

Avoid oxidizing agents.

Hazardous decomposition products

None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

Repeated exposure may cause skin dryness or cracking. May cause allergic skin reaction.

Eye Contact

May cause eye irritation.

Ingestion

May cause gastrointestinal irritation, nausea, vomiting, diarrhea.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Oral LD50 Rat >15 g/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred)

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

Immediate Effects

May cause allergic skin reaction.

Page 5 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Delayed Effects

Repeated exposure may cause skin dryness or cracking.

Irritation/Corrosivity Data

May cause eye irritation. Repeated exposure may cause skin dryness or cracking.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

May cause allergic skin reaction.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No information on significant adverse effects.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

Additional Data

No additional information is available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Harmful aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7					
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L					
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID					
Phosphorodithioic acid, O,O-di-C1- 14-alkyl esters, zinc salts	68649-42-3					
Fish:	LC50 96 h Pimephales promelas 1 - 5 mg/L [static]; LC50 96 h Pimephales promelas 10 - 35 mg/L [semi-static]					
Invertebrate:	EC50 48 h Daphnia magna 1 - 1.5 mg/L IUCLID					

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Page 6 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Kleen Performance Products regarding proper recycling or disposal.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transport. **IATA Information:** Not regulated for transport. **IMDG Information:** Not regulated for transport. **TDG Information:** Not regulated for transport.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

Further information

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: No Chronic Health: No Fire: No Pressure: No Reactivity: No

TSCA Inventory

All of the components of this product are listed on, or are automatically included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA inventory.

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

		NJ	CA	PA
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters,	68649-42-03	YES	YES	YES
zinc salts				

No components are listed under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

Page 7 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Component Analysis - Inventory

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

US	CA	AU	CN	E	U	JP - ENCS	JP - ISHL	r	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Ye	s E	IN	No	No		Yes	No
KR - REACH CCA			A	MX	NZ	PH	TH- TECI	TW	VN (Draft)	
No			Yes	Yes	Yes	No	Yes	Yes		

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

US	CA	AU	CN	E	U	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	s E	IN	Yes	Yes		Yes	No
KR - REACH CCA			MX	NZ	РН	TH- TECI	TW	VN (Draft)		
No			Yes	Yes	Yes	No	Yes	Yes		

Highly refined mineral oil (C15-C50) (Mixture)

US	CA	AU	C	N	EU	JP - ENCS	JP - ISHL		KR KECI - Annex	KR KECI - Annex 2
No	No	No	N	0	No	No	No		No	No
KR - REACH CCA			MX	NZ	РН	TH- TECI	TW	VN (Draft)		
No		No	No	No	No	No	No			

01154100-5327P (Trade Secret)

US	CA	AU	C	N 1	EU	JP - ENCS	JP - ISHL		KR KECI - Annex	KR KECI - Annex 2
No	No	No	N	o l	No	No	No		No	No
KR - REACH CCA			MX	NZ	PH	TH- TECI	TW	VN (Draft)		
No		No	No	No	No	No	No			

Page 8 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

US	CA	AU	CN	E	U	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	E	IN	No	No		Yes	No
KR - REACH CCA			\]	MX	NZ	PH	TH- TECI	TW	VN (Draft)	
No		,	Yes	Yes	Yes	No	Yes	Yes		

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 1 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes:

2019-02: Update to Section 3, Composition, update to Branding and format.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC -European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F -Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG -International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID -International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK -Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne-Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc -Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG -Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Page 9 of 10 Rev. 2/19

Material Name: Performance Plus Natural Gas SAE 15W-40 CNG+ SDS ID: 820383

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Kleen Performance Products assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Page 10 of 10 Rev. 2/19