Material Safety Data Sheet TRIC



Paraffin Oil

Section 1. Product and Company Identification

Product name Paraffin Oil : PX0047 Product code

Svnonvm : Mineral Oil, Paraffin Oil

: Other non-specified industry: Analytical reagent. **Material uses**

Manufacturer : EMD Chemicals Inc.

P.O. Box 70

480 Democrat Road Gibbstown, NJ 08027

856-423-6300 Technical Service Monday - Friday: 8:00 - 5:00 PM

Validation date : 1/12/2011. **Print date** : 1/12/2011.

Section 2. Hazards Identification

Physical state : Liquid. (Oily liquid.)

Odor : Odorless.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

: CAUTION! **Emergency overview**

CAUSES EYE IRRITATION.

MAY CAUSE RESPIRATORY TRACT AND SKIN IRRITATION.

MAY BE HARMFUL IF SWALLOWED OR INHALED.

MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: RESPIRATORY TRACT,

SKIN, EYE, LENS OR CORNEA.

ASPIRATION HAZARD.

Do not ingest. Avoid contact with skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after

handling.

Routes of entry : Inhalation. Ingestion.

Potential acute health effects

: Irritating to eyes. Eyes

Skin : Moderately irritating to the skin.

: Moderately irritating to the respiratory system. Inhalation

Ingestion Harmful if swallowed.

Carcinogenic effects : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Mutagenic effects** Teratogenicity / : No known significant effects or critical hazards.

Medical conditions

Reproductive toxicity

: Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or

prolonged exposure to the substance can produce lung damage. Repeated or aggravated by overexposure

prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to the substance can produce target organs

See toxicological information (section 11)

Continued on Next Page

Paraffin Oil PX0047 Page: 2/6

Section 3. Composition/Information on Ingredients

United States

% by Weight Name **CAS** number Paraffin Oil 8012-95-1

Section 4. First Aid Measures

Eye contact : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting

the upper and lower eyelids. Check for and remove any contact lenses. Get medical

attention.

Skin contact : Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes.

Get medical attention. Remove contaminated clothing and shoes. Wash clothing before

reuse. Clean shoes thoroughly before reuse.

Inhalation : Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if

breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouthto-mouth resuscitation. Get medical attention if symptoms occur. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

: Wash out mouth with water. Remove dentures if any. Move exposed person to fresh Ingestion

air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical

attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

Section 5. Fire Fighting Measures

Flammability of the product: No specific hazard.

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

: None known. Not suitable : Not available.

Special exposure hazards

Special protective : Fire-fighters should wear appropriate protective equipment and self-contained breathing equipment for fire-fighters

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental Release Measures

Personal precautions : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains **Environmental precautions**

and sewers.

Methods for cleaning up : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Continued on Next Page

Paraffin Oil PX0047 Page: 3/6

Section 7. Handling and Storage

Handling: Do not ingest. Avoid contact with eyes, skin and clothing. Keep container closed. Use

only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after

handling.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8. Exposure Controls/Personal Protection

<u>Product name</u> <u>Exposure limits</u>

United States

Paraffin Oil ACGIH TLV (United States, 1/2007).

STEL: 10 mg/m³ 15 minute/minutes.

TWA: 5 mg/m³ 8 hour/hours.

NIOSH REL (United States, 12/2001).

STEL: 10 mg/m³ 15 minute/minutes. Form: Mist TWA: 5 mg/m³ 10 hour/hours. Form: Mist **OSHA PEL (United States, 11/2006).**

TWA: 5 mg/m³ 8 hour/hours.

OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hour/hours. Form: Mist

Consult local authorities for acceptable exposure limits.

Engineering measures: No special ventilation requirements. Good general ventilation should be sufficient to

control airborne levels. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep

worker exposure below any recommended or statutory limits.

Personal protection

Eyes : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists,

gases or dusts.

Recommended: safety glasses with side-shields

Skin : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling

this product.

Body: Recommended: lab coat

Respiratory: Use a properly fitted, air-purifying or air-fed respirator complying with an approved

standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is

necessary. Recommended: nitrile rubber

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate

techniques should be used to remove potentially contaminated clothing. Wash

contaminated clothing before reusing. Ensure that eyewash stations and safety showers

are close to the workstation location.

Section 9. Physical and Chemical Properties

Physical state : Liquid. (Oily liquid.)

Flash point : Closed cup: 192.85°C (379.1°F).

Auto-ignition temperature : 259.85 to 370.85°C (499.7 to 699.5°F)

Color : Colorless to light yellow. Clear.

Odor : Odorless.

Boiling/condensation point : 360°C (680°F) **Melting/freezing point** : -17.8°C (0°F)

Relative density : 0.8 to 0.9 (Water = 1)

Continued on Next Page

Section 10. Stability and Reactivity

Stability and reactivity: The product is stable.

Incompatibility with various: Reactive or incompatible with the following materials: oxidizing materials.

substances

Hazardous polymerization : Will not occur.

Section 11. Toxicological Information

Toxicity data

Chronic effects on humans : May cause damage to the following organs: upper respiratory tract, skin, eye, lens or

cornea.

Other toxic effects on

humans

: Very hazardous in case of eye contact (irritant).

Hazardous in case of inhalation (lung irritant).

Specific effects

Carcinogenic effects : No known significant effects or critical hazards.

Mutagenic effects : No known significant effects or critical hazards.

Teratogenicity / : No known significant effects or critical hazards.

Reproductive toxicity

Sensitization

Ingestion: No known significant effects or critical hazards.Inhalation: Moderately irritating to the respiratory system.

Eyes: Irritating to eyes.

Skin: Moderately irritating to the skin.

Section 12. Ecological Information

Ecotoxicity data

United States

Product/ingredient nameSpeciesPeriodResultParaffin OilLepomis macrochirus (LC50)96 hour/hours>100 mg/lOncorhynchus mykiss (LC50)96 hour/hours>100 mg/l

Environmental precautions: No known significant effects or critical hazards.

Section 13. Disposal Considerations

Waste disposal

The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Paraffin Oil PX0047 Page: 5/6

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
DOT Classification	-	CHEMICALS, N.O.S.	-	-		Not available.

PG*: Packing group

Section 15. Regulatory Information

United States

HCS Classification : Irritating material

Target organ effects

U.S. Federal regulations : TSCA 8(b) inventory: Listed

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Paraffin Oil

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Paraffin

Oil: Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 accidental release prevention: No products were found. Clean Air Act (CAA) 112 regulated flammable substances: No products were found. Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

State regulations : Pennsylvania RTK: Paraffin Oil: (generic environmental hazard)

Massachusetts RTK: Paraffin Oil

New Jersey: Paraffin Oil

<u>Ingredient name</u> <u>Cancer</u> <u>Reproductive</u> <u>No significant risk</u> <u>Maximum</u>

<u>level</u> <u>acceptable dosage</u>

level

Paraffin Oil Yes. No. No. No.

Canada

WHMIS (Canada) : Class D-2B: Material causing other toxic effects (Toxic).

CEPA DSL/CEPA NDSL : CEPA DSL: Paraffin Oil

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

EU regulations

Risk phrases: This product is not classified according to EU legislation.

International regulations

International lists : Australia (NICNAS): Paraffin Oil

China: Paraffin Oil

Korea (TCCL): Paraffin Oil

Philippines (RA6969): Paraffin Oil

Paraffin Oil PX0047 Page: 6/6

Section 16. Other Information

Label requirements : CAUTION!

CAUSES EYE IRRITATION.

MAY CAUSE RESPIRATORY TRACT AND SKIN IRRITATION.

MAY BE HARMFUL IF SWALLOWED OR INHALED.

MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: RESPIRATORY TRACT,

SKIN, EYE, LENS OR CORNEA.

ASPIRATION HAZARD.

National Fire Protection Association (U.S.A.)

Health 0 0 Instability
Special

Notice to reader

The statements contained herein are based upon technical data that EMD Chemicals Inc. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD CHEMICALS INC. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.