

SAFETY DATA SHEET

LIQUITEX SOLUVAR GLOSS VARNISH

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name LIQUITEX SOLUVAR GLOSS VARNISH

Product number 63111

Recommended use of the chemical and restrictions on use

Application Varnish for Oil Painting Varnish for Acrylic Painting

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier ColArt Americas Inc.
11 Constitution Avenue
Piscataway
New Jersey 08855 - 1396
USA
1-732-562-0770
R.Enquiries@colart.co.uk

Contact Person Regulatory Manager

Manufacturer

Emergency telephone number

Emergency telephone For health information only call 1-800-628-3385 Piscataway NJ 08855.

2. Hazard(s) identification

Classification of the substance or mixture


Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Sens. 1 - H317 Repr. 2 - H361d STOT RE 1 - H372

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

LIQUITEX SOLUVAR GLOSS VARNISH

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
 P261 Avoid breathing vapor/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P273 Avoid release to the environment.
 P302+P352 If on skin: Wash with plenty of water.
 P308+P313 If exposed or concerned: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with national regulations.

Contains Stoddard solvent, Toluene

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Stoddard solvent	30-60%
CAS number: 8052-41-3	
Classification	
Flam. Liq. 3 - H226	
STOT RE 1 - H372	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
Alkane, C9-12 iso-	10-30%
CAS number: 90622-57-4	
REACH registration number: 01-2119471991-29xxx	
Classification	
Flam. Liq. 3 - H226	
Asp. Tox. 1 - H304	
Aquatic Chronic 4 - H413	
distillates (petroleum), hydrotreated light	5-10%
CAS number: 64742-47-8	
REACH registration number: 01-2119457736-27-0001	
Classification	
Asp. Tox. 1 - H304	
Pine oil	1-5%
CAS number: 8002-09-3	
Classification	
Acute Tox. 4 - H302	
Eye Irrit. 2 - H319	

LIQUITEX SOLUVAR GLOSS VARNISH

Nonane	1-5%
CAS number: 111-84-2	REACH registration number: 01-2119463259-31-XXXX
M factor (Acute) = 1	
Classification	
Flam. Liq. 3 - H226	
Aquatic Acute 1 - H400	
1,2,4-TRIMETHYLBENZENE	1-5%
CAS number: 95-63-6	
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
Aquatic Chronic 2 - H411	
Toluene	<1%
CAS number: 108-88-3	REACH registration number: 01-2119471310-51-XXXX
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Repr. 2 - H361d	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 3 - H412	
Derivative of Benzotriazole; EC No. 400-830-7; Index No. 607-176-00-3	<1%
CAS number: —	
Classification	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information

Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

LIQUITEX SOLUVAR GLOSS VARNISH

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	Rinse with water.
Eye contact	Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	No specific symptoms known. May be slightly irritating to eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
-------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
--------------------------------------	-------------------------------------------------------------------------------------------------------------

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
-----------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.
------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

LIQUITEX SOLUVAR GLOSS VARNISH

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Suspected of damaging the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store locked up. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class Flammable liquid storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Exposure controls

LIQUITEX SOLUVAR GLOSS VARNISH

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

Respiratory protection

No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

Environmental exposure controls

Keep container tightly sealed when not in use. Avoid release to the environment.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid
Color	Colorless.
Odor	Characteristic.
pH	Not applicable.
Flash point	41.°C CC (Closed cup).
Upper/lower flammability or explosive limits	: 0.9
Vapour pressure	2. mm Hg @ °C
Solubility(ies)	<0.1 @ °C Insoluble in water
Auto-ignition temperature	>250°C
Viscosity	134 s @ °C
Other information	Not available.

10. Stability and reactivity

Reactivity

There are no known reactivity hazards associated with this product.

Stability

Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

LIQUITEX SOLUVAR GLOSS VARNISH

Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing agents.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
Materials to avoid	Oxidizing materials. Acids - oxidizing.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	25,773.2

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
---------------------------------------	------------------------------------------------------------------

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (gases ppm)	266,665.09
ATE inhalation (vapours mg/l)	651.85
ATE inhalation (dusts/mists mg/l)	88.89

Skin corrosion/irritation

Animal data	Repeated exposure may cause skin dryness or cracking.
--------------------	-------------------------------------------------------

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.
--------------------------------------	------------------------------------------------------------------

Respiratory sensitisation

Respiratory sensitisation	Based on available data the classification criteria are not met.
----------------------------------	------------------------------------------------------------------

Skin sensitisation

Skin sensitisation	Based on available data the classification criteria are not met.
---------------------------	------------------------------------------------------------------

Germ cell mutagenicity

Genotoxicity - in vitro	Based on available data the classification criteria are not met.
--------------------------------	------------------------------------------------------------------

Carcinogenicity

Carcinogenicity	Based on available data the classification criteria are not met.
------------------------	------------------------------------------------------------------

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
------------------------------------------	------------------------------------------------------------------

Reproductive toxicity - development

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

LIQUITEX SOLUVAR GLOSS VARNISH

STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	STOT RE 1 - H372 Causes damage to organs through prolonged or repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>General information</u>	
General information	Avoid contact during pregnancy/while nursing. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin Contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	No specific symptoms known.
Acute and chronic health hazards	Gas or vapor is harmful on prolonged exposure or in high concentrations.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.

12. Ecological Information

Ecotoxicity	Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.
<u>Toxicity</u>	
Toxicity	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
Acute toxicity - fish	Not determined.
Acute toxicity - aquatic invertebrates	Not determined.
Acute toxicity - aquatic plants	Not determined.
Acute toxicity - microorganisms	Not determined.
<u>Persistence and degradability</u>	
Persistence and degradability	The degradability of the product is not known.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
<u>Mobility in soil</u>	
Mobility	No data available.
<u>Other adverse effects</u>	
Other adverse effects	None known.

13. Disposal considerations

Waste treatment methods

LIQUITEX SOLUVAR GLOSS VARNISH

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

14. Transport information

UN Number

UN No. (DOT) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN proper shipping name

Proper shipping name (DOT) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Transport hazard class(es)

IMDG Class 3

ICAO class/division 3

Transport labels



Packing group

DOT pack group III

IMDG packing group III

ICAO packing group III

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-E, S-E

15. Regulatory information

LIQUITEX SOLUVAR GLOSS VARNISH

Regulatory Status

This product has been evaluated by a toxicologist and labelled for acute and chronic health hazards in accordance with the Labelling of Hazardous Art Materials Regulation and Federal Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conforms to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects.

This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe use instructions should be observed.

WARNING: COMBUSTIBLE. MAY BE HARMFUL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT.

Contains: PETROLEUM DISTILLATES

PRECAUTIONS: Keep away from eyes. Avoid ingestion. Do not store or use near heat or flame. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If swallowed, get prompt medical attention. For Health information only call 1-800-628-3385 Piscataway NJ 08855.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

None of the ingredients are listed or exempt.

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

LIQUITEX SOLUVAR GLOSS VARNISH

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

Massachusetts "Right To Know" List

None of the ingredients are listed or exempt.

Rhode Island "Right To Know" List

None of the ingredients are listed or exempt.

Minnesota "Right To Know" List

None of the ingredients are listed or exempt.

New Jersey "Right To Know" List

None of the ingredients are listed or exempt.

Pennsylvania "Right To Know" List

None of the ingredients are listed or exempt.

Inventories

US - TSCA

None of the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Training advice	Read and follow manufacturer's recommendations.
Revision date	7/31/2015
Revision	3
Supersedes date	18/09/2012
Hazard statements in full	<p>H225 Highly flammable liquid and vapor. H226 Flammable liquid and vapor. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.</p>

LIQUITEX SOLUVAR GLOSS VARNISH

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.