



[home](#) [msds search](#) [browse manufacturers](#) [browse products](#) [shopping](#) [contact us](#)

Select Language ▼

OSHA Safety Keep Your Employees Safe & Up To Date On OSHA Industry Standards! www.safetyservicescompany.com

Download ansi a10.11 Download ANSI ASSE Standards safety engineering standards webstore.ansi.org/

OSHA PPE Requirements Free guide to PPE requirements for Top 12 major hazard categories. www.Duralab.com AdChoices >

765-1322 LIQUID TIRE BUFFER & CLEANER

[Save as PDF](#)

MSDS Number

BXHPH

National Stock Number

6850-01-198-4444

Product Name

765-1322 LIQUID TIRE BUFFER & CLEANER

Manufacturer

CAMEL TIRE CARE PRODUCTS DIV OF BRIDGE PRODUCT INC

Product Identification

Product ID:765-1322 LIQUID TIRE BUFFER & CLEANER

MSDS Date:08/05/1993

FSC:6850

NIIN:01-198-4444

MSDS Number: BXHPH

Responsible Party

Company Name:CAMEL TIRE CARE PRODUCTS DIV OF BRIDGE PRODUCT INC

Address:4803 HAROLD ABITZ DR

Box:769

City:MUSKOGEE

State:OK

ZIP:74402-0769

Country:US

Info Phone Num:918-687-5427 / FAX 918-682-1635

Emergency Phone Num:918-687-5427

CAGE:97789

Contractor

Company Name:BALKAMP INC

Address:2601 S HOLT ROAD

Box:City:INDIANAPOLIS

State:IN

ZIP:46241

Country:US

Phone:317-244-7241

CAGE:70842

Company Name:BRIDGE PRODUCT INC/CAMEL TIRE CARE PRODUCTS DIV

Address:5005 45TH E

Box:769


City:MUSKOGEE

State:OK

ZIP:74403-5000

Country:US

Phone:918-687-5427



CAGE:97789

Ingredients

Ingred Name:TRICHLOROETHYLENE (SARA 313) (CERCLA)

CAS:79-01-6

RTECS #:KX4550000

Fraction by Wt: 50.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM; Z-2

ACGIH TLV:50 PPM/100STEL;A5;95

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:METHYLENE CHLORIDE (SARA 313) (CERCLA)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 30.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

ACGIH TLV:50 PPM, A2; 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 16.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 4.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: <1.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:1,2-BUTYLENE OXIDE (SARA 313) (CERCLA)

CAS:106-88-7

RTECS #:EK3675000

Fraction by Wt: TRACE

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:STABILIZERS

Fraction by Wt: TRACE

Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS

Other REC Limits:NONE RECOMMENDED



	Cables To Go 43036 Cable Ties 4-inch... Cables To Go New \$2.79
	RhinoGear 11930 Tire Hugger Wheel Ch... Blitz New \$8.99
	8' Plastic Cable Zip Ties 100-Pack Generic New \$3.46
	Magna Cart Elite 2 Hand Truck Welcom New \$39.99
	Softride 26260 Velcro Soft Wrap - Pa... Softride New \$7.19
	Velcro Cable Tie Roll 3/4\" x 5 yard... CbiWhl New \$3.75

Privacy Information

Open PDF

Price: Free
Browsers: IE/Firefox/Chrome/Safari/Opera
OS: Windows 7/XP/Vista/NT
Software: PDF Expert

 **Download**

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: EYE: MODERATE IRRIT, SLIGHT CORNEAL INJURY. SKIN: IRRIT, BURN, REPEAT DRY/FLAKE. EXTENSIVE CONTACT INTENSE BURNING SENSATION. ABSORPTION: INCREASE BLOOD CONCENTRATION, NUMBNESS OF FINGERS. INGEST: ENTER THRU LUNG RAPIDLY ABSORBED-INJURE OTHER BODY SYSTEMS. INHAL: UNCONSCIOUS, DEATH, UPPER RESPIRATORY IRRITATION, INCREASE SENSITIVITY TO EPINEPHRINE, IRREGULAR HEARTBEATS.
Explanation of Carcinogenicity: PER MSDS: CARCINOGEN NTP/OSHA: NOT ESTABLISHED, IARC: UNKNOWN.
Effects of Overexposure: TEMP REDDENING OF SKIN (DEGREASER'S FLUSH), DIZZINESS, DRUNKEN IMPAIRMENT OF BLOOD ABILITY TO TRANSPORT OXYGEN. ALCOHOL CONSUMED BEFORE/AFTER EXPOSURE INCREASES ADVERSE EFFECTS & CNS & PERIPHERAL EFFECTS. EYE: PAIN, IRRITATION, CORNEAL INJURY. SKIN: IRRITATION, BURN, DRY, FLAKE, COLD/NUMB FEELING. INHAL: UNCONSCIOUS, DEATH, UPPER RESPIRATORY IRRITATION.
Medical Condition Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid: EYE: IRRIGATE IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH OFF IN FLOWING WATER/SHOWER. REMOVE CONTAMINATED CLOTHING. INGEST: DO NOT INDUCE VOMIT. CALL DRUG AND/OR TRANSPORT TO EMERGENCY FACILITY IMMEDIATELY. INHAL: REMOVE TO FRESH AIR. DO NOT BREATH. GIVE MOUTH-TO-MOUTH RESUSCITATION. DIFFICULT BREATHING: GIVE OXYGEN. CALL DRUG. NOTE TO DRUG: BECAUSE RAPID ABSORPTION MAY OCCUR THROUGH LUNGS IF ASPIRATED & CAUSE SYSTEMIC EFFECTS DECISION OF WHETHER TO INDUCE SUPPLEMENTAL VENTILATION.

Fire Fighting

Flash Point: >140°F, >60°C
Lower Limits: 1.0 @ 212°F
Upper Limits: 44.8 @ 212°F
Extinguishing Media: WATER FOG, DRY CHEMICAL, FOAM, CO2. DO NOT USE DIRECT WATER STREAM.
Fire Fighting Procedures: USE WATER SPRAY TO COOL NEARBY CONTAINERS/STRUCTURES EXPOSED TO FIRE. WEAR POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS OR AIR SUPPLIED FULLY ENCAPSULATING SUIT.
Unusual Fire/Explosion Hazard: MAY FORM FLAMMABLE VAPOR/AIR MIXTURES. AVOID ACCUMULATION OF WATER-PRODUCED MAY FLOAT ON WATER & REIGN ON SURFACE OF WATER. REMOVE ALL IGNITION SOURCES. VAPOR HEAVIER THAN SUPPLEMENTAL VENTILATION.

Accidental Release

Spill Release Procedures: SMALL: MOP/WIPE/SOAK UP IMMEDIATELY. REMOVE TO OUTDOORS. LARGE: EVACUATE AREA. CONTAIN LIQUID. TRANSFER TO CLEAN METAL CONTAINERS. KEEP OUT OF WATER SUPPLY. ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: HANDLE WITH REASONABLE CARE. AVOID BREATHING VAPOR. STORE IN COOL DRY PLACE. CONCENTRATION VAPOR HEAVIER THAN AIR/COLLECT IN LOW AREAS- DO NOT ENTER WITHOUT PROTECTIVE EQUIPMENT & OBSERVE
Other Precautions: 1ST AID: NO SPECIFIC ANTIDOTE. CARBOXYHEMOGLOBINEMIA MAY

AGGRAVATE ANY PRE-EXISTING CONDITION SENSITIVE TO DECREASE IN AVAILABLE O₂ SUCH AS CHRONIC LUNG DISEASE, CORONARY ARTERY DISEASE OR ANEMIAS. USE WITH ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection: ATM LEVELS SHOULD BE MAINTAINED WHEN RESP PROT REQUIRED FOR CERTAIN OPERATIONS USE APPROVED

AIR-PURIFYING RESP. FOR EMERG/OTHER CONDITIONS WHERE EXPO GUIDELINE GREATLY EXCEEDS (CONFINED, POORLY VENTILATED) USE APPROVED + PRESS SCBA.

Ventilation: CNTRL AIRBORNE CONCEN FOR SOME OPERATION. LETHAL CONCEN MAY EXIST IN POOR VENTILATED AREA

Protective Gloves: SELECTION DEPENDS ON OPERATION. REQUIRE

Eye Protection: USE CHEMICAL GOGGLES.

Other Protective Equipment: USE PROT CLOTH IMPERVIOUS TO MATL. SELECTION OF BOOTS, APRON, FULL-BODY SUIT WILL DEPEND ON OPERATION.

Work Hygienic Practices: CLEAN WELL CONTAMINATED CLOTH BEFORE REUSE. WASH WELL AFTER HANDLING.

Supplemental Safety and Health

FIRE/EXPLO HAZ: AIR; TRAVEL ALONG SURFACE TO DISTANT SOURCE OF IGN; FLASHBACK. 1ST AID: VOMIT OR NOT SHOULD BE MADE BY DR. IF LAVAGE PERFORMED SUGGEST ENDOTRACHEAL &/OR ESOPHAGEAL CNTRL. LUNG ASPIRATION DANGER MUST BE WEIGHED AGAINST TOXICITY WHEN CONSIDERING EMPHYSEMA. EXPO MAY INCREASE MYOCARDIAL IRRIT. NO SYMPATHOMIMETIC

Chemical Properties

HCC: F5

Boiling Pt: B.P. Text: 104F, 40C

Vapor Pres: 25-355

Vapor Density: >1

Spec Gravity: 1.3 25/25C

Solubility in Water: SLIGHT @ 25C

Appearance and Odor: COLORLESS LIQUID, IRRITATING ODOR @ HIGH CONCENTRATIONS.

Percent Volatiles by Volume: >85

Stability

Stability Indicator/Materials to Avoid: YES

STRONG BASES, CAUSTIC SODA, CAUSTIC POTASH, OXIDIZERS, METALLIC AL & ZN POWDERS, AMINES POSSIBLY SODIUM, POTASSIUM, MAGNESIUM

Stability Condition to Avoid: OPEN FLAMES/WELD ARC/OTHER HI TEMP SOURCES. HYDROLYSIS/

Hazardous Decomposition Products: FIRE/HI TEMP: CO, CO₂, HCL, VERY SMALL AMTS OF PHOSGENE & CL. CATALYZED BY METAL CHLORIDES, 1,1,1-TRICHLOROETHANE EFFECT STABILIZER

Disposal

Waste Disposal Methods: UNUSED CONTAINERS PREFERRED. SEND TO LICENSED RECLAIMERS; PERMITTED INCINERATORS. ANY DISPOSAL PRACTICE MUST BE IN COMPLIANCE W/ FED/STATE/LOCAL LAWS/REGS. EMPTY CONTAINER CAN HAVE RESIDUES/GAS/MIST SUBJECT TO PROPER WASTE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.