ACE MATERIAL SAFETY DATA SHEET Hardware

HEALTH FLAMMABILITY 2 FOR COATINGS, RESINS AND RELATED MATERIALS REACTIVITY

PERSONAL PROTECTION C

1

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA 174)

PRODUCT: 211A100, 110, 115, 116, 119, 200, 210, 215

FIVE STAR ALKYD/OIL BASE FLOOR ANDTRIM ENAMEL

SECTION I

Manufacturer's Name: **Emergency Telephone Number**

Paint Division, Ace Hardware Corporation Address (Number, Street. City. State, and ZIP Code)

Telephone Number for Information

(708) 990-6600

21901 S. Central Ave.

(708) 720-0600 Date Prepared

Matteson, IL 60443

JULY 1, 1997 Signature of Preparer (optional)

10Mg/M3

0.4

SESTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components:

Aluminum Hydroxide

(Chemical Identity: Common Name(s)) OSHA PEL ACGIH TLV %(optional) Titanium Dioxide CAS# 13463-67-7 10 Mg/M3 10 Mg/M3 28.5 Calcium Carbonate CAS# 1317-65-3 15 Mg/M3 10 Mg/M3 9.3 Yellow Iron Oxide CAS# 20344-49-4 None Est. None Est. 3.9 AZO Red Pigment CAS# 2425-85-6 None Est. None Est. 8.5 Red Iron Oxide CAS# 1309-37-1 5Mg/M3 5Ma/M3 3.8 Mineral Spirits CAS# 64742-47-8 500 PPM 100 PPM 52.8 Amorphous Silica CAS# 7631-86-9 10Mg/M3 6Mg/M3 Ethyl Alcohol CAS# 64-17-5 1000 PPM 1000 PPM 0.4 Soya Lecithin CAS# 8002-43-5 0.8

15 Mg/M3

SECTION III-PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Specific Gravity: (H20 = 1)

308 F 1.07

CAS# 1328-53-6

Melting Point: Vapor Pressure (mm Hg):

Evaporation Rate (Butyl Acetate = 1) Vapor Density (Air = 1): Slower Than Ether HeavierThan Air

Solubility in water: Not Applicable

Appearance and Odor:

Colored pigmented liquid with solvent odor.

Section IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) Flammable Limits LEL UEL

105 F PMCC N/A N/A 0.9

Extinguisthing Media:

Non Combustible. For dry solids use water, foam, CO2, dry chemicals

Special Fire Fighting Procedures:

Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion to extreme heat.

Unusual Fire And Explosion Hazards:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Heat may cause pressure build-up in closed containers. Water may be used to cool.

Section V- REACTIVITY DATA

Stability: Conditions to Avoid:

Stable

Incombatibility (Materiels to Avoid):

No hazardous reactions are expected under normal use.

Hazardous Decomposition or Byproducts: Carbon dioxide and carbon monoxide

Hazardous Polymerzation: Conditions to Avoid:

Will not Occur

Section VI - HEALTH HAZARDS DATA

Routes of Entry: Inhalation? Skin? Ingestion?

Possible Possible Possible

Health Hazards (Acute and Chronic):

Acute: Irritation of eyes, skin and respiratory system may occur on overexposure. May also cause nervous system depression.

Chronic: Reports have associated repeated and prolonged occupational overexposure to solvents with premanent brain and nervous system damage.

Carcinogenity: NTP? IARC Monographs OSHA Regulated?

No No No

Signs and Symptoms of Exposure:

Headaches, dizziness, nausea and loss of coordination are indications of excessive exposure to vapors or spray mists.

Medical Conditions Generally Aggravated by Exposure:

None generally recognized

Emergency and First Aid Procedures:

If inhaled - Remove from exposure - restore breathing - keep warm and quiet. If on skin wash affected area thoroughly with soap and water - flush eyes with large amounts of water for 15 minutes. Get medical attemtion.

Section VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken In Case Material Is Released or Spilled: Remove all sources of ignition. Ventilate and remove with inert absorbent.

Waste Disposal Method:

Incinerate in approved facility. Do not incinerate closed containers. Dispose of in accordance with Federal State and Local regulations.

Precautions To Be Taken In Handling and Storage:

Contents are combustible. keep away from heat and open flame. use approved bonding and grounding procedures. Transfer only to approved, poperly marked containers.

Other Precautions:

Keep out of the reach of children. Intentional misuse by deliberately inhaling the contents can be harmful or fatal.

Section VIII - CONTROL MEASURES

Respiratory Protection (Specify Type):

Properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA.

Ventilation: Local Exhaust Special

Preferable

Mechanical (General) Other

Protective Gloves:

Eye Protection:
Safety spectacles w/unperforated side shields. Those recommended for use with

Sect. II materials.

Other Protective Clothing or Equipment:

Work Hygienic Practices: