

Thermal Poly 32 Floor Finish

Page: 1
Printed: 07/21/2015

Revision: 03/23/2015 Supersedes Revision: 11/13/2014

1. Product and Company Identification

Product Code: 09930

Product Name: Thermal Poly 32 Floor Finish

Company Name:GenlabsPhone Number:5568 Schaefer Ave.1 (909)591-8451

5568 Schaefer Ave. Chino, CA 91710

Web site address: www.genlabscorp.com

Emergency Contact: Chemtrec 1 (800)424-9300

Recommended Use: Floor Finish

Intended Use: For sale to, use and storage by service persons only.

2. Hazards Identification

Serious Eye Damage/Eye Irritation, Category 2A

Aquatic Toxicity (Chronic), Category 3
Acute Toxicity: Oral, Category 5
Skin Corrosion/Irritation, Category 3
Acute Toxicity: Inhalation, Category 5

Target Organ Systemic Toxicity (single exposure), Category 3

Aquatic Toxicity (Acute), Category 2



GHS Signal Word: Warning

GHS Hazard Phrases: Causes serious eye irritation.

Harmful to aquatic life with long lasting effects.

May be harmful if swallowed. Causes mild skin irritation. May be harmful if inhaled. May cause respiratory irritation.

Toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

GHS Precaution Phrases: Wash hands thoroughly after handling.

Keep out of reach of children.

Wear protective gloves, protective clothing, eye protection, face protection.

Avoid release to the environment. Avoid breathing fumes and spray mist.

Use only outdoors or in a well-ventilated area.

GHS Response Phrases: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If eye irritation persists, get medical attention immediately.

If on skin (or in hair): Wash with plenty of soap and water. If skin irritation occurs, get

medical attention immediately.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

GHS Storage and Disposal

Phrases:

Dispose of contents and container according to the local, city, state and federal

regulations.

Store in cool dry place at room temperature away from direct sunlight.



Thermal Poly 32 Floor Finish

Page: 2
Printed: 07/21/2015

Revision: 03/23/2015 Supersedes Revision: 11/13/2014

Potential Health Effects (Acute and Chronic):

Inhalation: High vapor concentrations may cause drowsiness. May cause respiratory tract irritation.

Skin Contact: May cause allergic skin reaction.

Eye Contact: Causes eye irritation.

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea.

3. Composition/Information on Ingredients

| CAS# | Hazardous Components (Chemical Name) | Concentration |
|------------|--------------------------------------|---------------|
| 25987-66-0 | Acrylic acid polymer | Proprietary |
| 111-90-0 | Diethylene glycol monoethyl ether | Proprietary |
| 25265-77-4 | Texanol | Proprietary |
| 78-51-3 | Ethanol, 2-Butoxy-, phosphate (3:1) | Proprietary |
| 1314-13-2 | Zinc oxide | Proprietary |

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical aid.

Remove from exposure and move to fresh air immediately.

In Case of Skin Contact: Remove contaminated clothing and shoes. Get medical aid if irritation develops and

persists. Wash clothing before reuse. Flush skin with plenty of water for at least 15

minutes while removing contaminated clothing and shoes.

In Case of Eye Contact: Get medical aid immediately. In case of contact, immediately flush eyes with copious

amounts of water for at least 15 minutes.

In Case of Ingestion: Never give anything by mouth to an unconscious person. If victim is conscious and alert,

give 2-4 cupfuls of milk or water. If swallowed, wash out mouth with water provided person is conscious. Call a physician. If conscious and alert, rinse mouth and drink 2-4

cupfuls of milk or water.

Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: NE

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: NE

Suitable Extinguishing Media: Use water spray, alcohol foam, CO2, dry chemical.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use

water spray to keep fire-exposed containers cool.

Flammable Properties and

Hazards:

No data available.



Thermal Poly 32 Floor Finish

Page: 3

Printed: 07/21/2015

Revision: 03/23/2015

Supersedes Revision: 11/13/2014

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Provide ventilation. Prevent runoff

from entering drains, sewers, or streams.

7. Handling and Storage

Precautions To Be Taken in

Handling:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse.

Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid

ingestion and inhalation.

Precautions To Be Taken in

Storing:

Store in a cool, dry, well-ventilated area away from incompatible substances. Keep from

freezing.

8. Exposure Controls/Personal Protection

| CAS# | Partial Chemical Name | OSHA TWA | ACGIH TWA | Other Limits |
|------------|-------------------------------------|--------------------------|------------------|--------------|
| 25987-66-0 | Acrylic acid polymer | No data. | No data. | No data. |
| 111-90-0 | Diethylene glycol monoethyl ether | No data. | No data. | No data. |
| 25265-77-4 | Texanol | No data. | No data. | No data. |
| 78-51-3 | Ethanol, 2-Butoxy-, phosphate (3:1) | No data. | No data. | No data. |
| 1314-13-2 | Zinc oxide | PEL: 5 (fume); 15 (dust) | TLV: 2 mg/m3 (R) | No data. |

Respiratory Equipment

Always use a NIOSH approved respirator when necessary.

(Specify Type):

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. **Other Protective Clothing:** Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls

Facilities storing or utilizing this material should be equipped with an eyewash facility and

(Ventilation etc.):

a safety shower. Use adequate ventilation to keep airborne concentrations low.

Work/Hygienic/Maintenance

Wash thoroughly after handling. Wash contaminated clothing before reuse.

Practices:

9. Physical and Chemical Properties

Physical States:[] Gas [X] Liquid [] SolidAppearance and Odor:Opaque white liquid with bland odor.

Melting Point: NE

Boiling Point: > 212.00 F

Autoignition Pt: NE Flash Pt: NE

Explosive Limits: LEL: No data. UEL: No data.

Specific Gravity (Water = 1): 1.035

Density: 8.63 lbs/gal

fanlabs

Thermal Poly 32 Floor Finish

Page: 4 Printed: 07/21/2015

Revision: 03/23/2015 Supersedes Revision: 11/13/2014

NE **Bulk density:** NE

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): NE **Evaporation Rate:** ΝE 100% Solubility in Water:

Saturated Vapor

Concentration:

NP Viscosity:

7.5 - 9.0pH: **Percent Volatile:** No data. 0.0000 G/L VOC / Volume:

Particle Size: NE ΝE **Heat Value:** NE **Corrosion Rate:**

10. Stability and Reactivity

Unstable [] Stable [X] Stability:

NE

Conditions To Avoid -

Instability:

Extremes of temperature and direct sunlight. Strong acids, Strong oxidizing agents.

Incompatibility - Materials To Strong oxidizing agents, magnesium, chlorinated rubber.

Avoid:

Hazardous Decomposition Or Carbon monoxide, Carbon dioxide, Thermal decomposition may produce toxic fumes of

phosphorus oxides and/or phosphine. toxic fumes of zinc oxide. Byproducts:

Possibility of Hazardous

Reactions:

Will occur [] Will not occur [X]

Conditions To Avoid -None.

Hazardous Reactions:

11. Toxicological Information

No data available. **Toxicological Information:**

CAS# 111-90-0: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 25265-77-4: Carcinogenicity/Other

Information: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 1314-13-2: Not listed by ACGIH,

IARC, NTP, or CA Prop 65.

| CAS# | Hazardous Components (Chemical Name) | NTP | IARC | ACGIH | OSHA |
|------------|--------------------------------------|------|------|-------|------|
| 25987-66-0 | Acrylic acid polymer | n.a. | n.a. | n.a. | n.a. |
| 111-90-0 | Diethylene glycol monoethyl ether | n.a. | n.a. | n.a. | n.a. |
| 25265-77-4 | Texanol | n.a. | n.a. | n.a. | n.a. |
| 78-51-3 | Ethanol, 2-Butoxy-, phosphate (3:1) | n.a. | n.a. | n.a. | n.a. |
| 1314-13-2 | Zinc oxide | n.a. | n.a. | n.a. | n.a. |



Thermal Poly 32 Floor Finish

Page: 5 Printed: 07/21/2015

Revision: 03/23/2015 Supersedes Revision: 11/13/2014

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Dispose of contents and container according to the local, city, state and federal

regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Not Regulated.

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not Regulated.

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not Regulated.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

| CAS# | Hazardous Components (Chemical Name) | S. 302 (EHS) | S. 304 RQ | S. 313 (TRI) |
|------------|--------------------------------------|--------------|-----------|---------------|
| 25987-66-0 | Acrylic acid polymer | No | No | No |
| 111-90-0 | Diethylene glycol monoethyl ether | No | No | Yes-Cat. N230 |
| 25265-77-4 | Texanol | No | No | No |
| 78-51-3 | Ethanol, 2-Butoxy-, phosphate (3:1) | No | No | Yes-Cat. N230 |
| 1314-13-2 | Zinc oxide | No | No | Yes-Cat. N982 |

| CAS# | Hazardous Components (Chemical Name) | Other US EPA or State Lists |
|------------|--------------------------------------|---|
| 25987-66-0 | Acrylic acid polymer | CA PROP.65: No; CA TAC, Title 8: No |
| 111-90-0 | Diethylene glycol monoethyl ether | CA PROP.65: No; CA TAC, Title 8: TAC |
| 25265-77-4 | Texanol | CA PROP.65: No; CA TAC, Title 8: No |
| 78-51-3 | Ethanol, 2-Butoxy-, phosphate (3:1) | CA PROP.65: No; CA TAC, Title 8: TAC |
| 1314-13-2 | Zinc oxide | CA PROP.65: No: CA TAC. Title 8: TAC. Title 8 |



Thermal Poly 32 Floor Finish


Page: 6
Printed: 07/21/2015
Revision: 03/23/2015

Revision: 03/23/2015 Supersedes Revision: 11/13/2014

16. Other Information

Hazard Rating System:





HMIS:

Revision Date: 03/23/2015

Additional Information About PPE B: safety glasses; gloves.

This Product:

Company Policy or

Disclaimer:

The manufacturer believes the data set forth are accurate and makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion.